

WISI VX 26 H 0650

In-house/distribution amplifier, locally supplied



Description

The VX 26 H 0650 is a local feeding distribution amplifier with an integrated upstream amplifier and diplex filter. The settings can be adjusted via jumper or Q-steps and therefore an uninterrupted adjustment option is possible.

At a glance:

- Uninterruptible setting
- Aluminium die-cast housing
- Screwed, folding cover
- Integrated upstream amplifier and diplexer
- All settings via defined switching steps (Q-step) or jumper
- Output splitter (pluggable)
- Lightning protection of all RF-connections 4 kV

WISI Communications GmbH & Co. KG

Wilhelm-Sihn-Str. 5-7
75223 Niefern-Oeschelbronn, Germany

Phone: +49 7233 66-0, Fax - 350
E-Mail: export@wisi.de

Technical Modifications reserved. WISI cannot be held liable for any printing error. 1. März 2024, 8:56 AM

Technical data

Downstream	
Input measurement socket	-20 dB (Resistor)
Input return loss	>18 dB (-1 dB/oct.)
Frequency range downstream	85...1006 MHz
Gain downstream	41 dB
Frequency response	≤ ± 0.5 dB (85 - 862 MHz) ≤ ± 0.75 dB (862 - 1006 MHz)
Noise figure downstream	<6 dB up to 600 MHz; <9 dB up to 1006 MHz
Attenuator downstream	0...15 dB (1 dB-steps)
Equalizer downstream	0...22.5 dB (1.5 dB-steps)
Interstage attenuator downstream	0/5 dB (Jumper)
Interstage equalizer downstream	0/3/6/9 dB (Jumper)
Output level 1	112 dB μ V (CENELEC 42 channels, flat, CSO/CTB >60 dB)
Output level 2	115 dB μ V (CENELEC 42 channels, 6dB slope, bei CSO/CTB >60 dB)
Output level 3	107dB μ V (112 x 256QAM) flat
Output level 4	109dB μ V (112 x 256QAM) 12dB slope
Output test point	-20 dB (directional coupler)
Upstream	
Frequency range upstream	5...65 MHz
Gain upstream	24 dB
Frequency response	≤ ± 0.5 dB
Noise figure upstream	<6 dB
Attenuator upstream input	0...15 dB (1 dB-steps)
Attenuator upstream output	0...15 dB (1 dB-steps) + 5 dB Interstage Jumper
Equalizer US	0/3/6/9 dB (Interstage Jumper)
Output level US	109 dB μ V (BER ≤ 1E-8, MER ≥ 35 dB 5...65 MHz (6x64 QAM))
Connectors	
F-female	3 pcs.
General data	
Operating voltage AC	180...265 V (50/60 Hz)
Power consumption	<13 W
Dimensions (width x height x depth)	240 x 158 x 80 mm
Operating temperature range	-20...+55 °C
Protection class	IP66
Lightning protection	4 kV (EN61000-4-5, 1,2/50 μ s pulse)

Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	305 x 190 x 95 mm
Packaging volume sales unit	5.3 dm ³
Gross weight sales unit	1.8 kg
Shipping unit	1 pcs.
EAN	4010056184858
Article number	18485
Customs tariff number	85437030